RS1004K-2S

POE SWITCH



- Ultra High Speed Full Gigabit Connectivity:
- Features 4 *10/100/1000Mbps PoE Ports Delivering 14Gbps Switching Capacity For Seamless Zero-Latency Data Transmission In High Bandwidth Networks.
- Advanced Dual Gigabit SFP Uplink Slots:
- Specifically Designed With 2 Dedicated 1000Mbps SFP Ports For Long-Distance Fiber Expansion And Easy Device Cascading Up To 100km Without Congestion.
- Professional 72W PoE Power Budget:
- Fully Compliant With IEEE 802.3af/at Standards Delivering Up To 30W Per Port To Efficiently Support High-Definition IP Cameras Or Wireless Access Points.
- Stable External DC 48V Power Supply:
- Engineered With An External Power System To Reduce Internal Heat Generation Ensuring Stable 24/7 Operation And Easier Maintenance In Tight Security Boxes.
- Direct Source Factory With Custom Services:
- As A Professional Leading Network Hardware Manufacturer We Provide Competitive Wholesale Pricing CE FCC Certification And Comprehensive OEM ODM Customization.

Product Name	4 GE 2 SFP Full Gigabit PoE Switch
PORTS	4*10/100/1000Mbps POE 2*1000Mbps SFP
PoE Standard	IEEE802.3af/at
PoE Port	Port 1~4
Power supply	65W MAX 72 W
PoE Pinout	1/2 V+ 3/6 V-

PoE port output	15.4 W MAX 30W
Type of forwarding	Storage forwarding
Exchange capacity	14G
MAC Address	2K, auto-learning & auto-aging
Standards	IEEE802.3,IEEE802.3u,IEEE802.3ab,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at
Transmission Distance	10BASE-T: Cat3/4/5 ≤250m 100BASE-TX: Cat5 ≤100m 1000BASE-T: Cat5e/Cat6 ≤100m SFP: MM 550m / SM 20~100km
Power input	DC 48 V
Operating Environment	Operating Temp: - 15℃~55℃; Storage Temp: -40℃~70℃ Operating Humidity: 10%~90% RH; Storage Humidity: 5%~90% RH, non-condensing
Size (L*W*H)	137*68*35 155*105*75mm
Weight	0.32 / 0.56Kg
Lightning Protection	±4KV， IP30