RS1005K-1S

POE SWITCH



- High Speed 5 Port Full Gigabit Connectivity:
- Features 4 10/100/1000Mbps PoE Ports 1 Gigabit RJ45 Uplink And 1 Gigabit SFP Slot Delivering 10Gbps Switching Capacity For Seamless Data Transmission.
- Flexible Fiber And Ethernet Hybrid Uplinks:
- The Dual Uplink Design (1GE+1SFP) Provides Versatile Options For Local NVR Connection And Long-Distance Fiber Backhaul Up To 100km Supporting Complex Networking Needs.
- Professional 72W High Power PoE Budget:
- Fully Compliant With IEEE 802.3af/at Standards Delivering Up To 30W Per Port To Efficiently Support High-Definition IP Cameras Wireless Access Points And VoIP Devices.
- Rugged Metal Housing With Wide Temperature:
- Engineered In A Durable Metal Enclosure Supporting -15C To 55C Operating Range With Internal Power Supply And ±4KV Lightning Protection For Stable 24/7 Performance.
- Direct Source Factory With Custom Services:
- As A Professional Leading Network Hardware Manufacturer We Provide Competitive Wholesale Pricing CE FCC Certification And Comprehensive OEM ODM Customization.

Product Name	4 Port PoE + 1 GE + 1 SFP PoE Switch
PORTS	4*10/100/1000Mbps POE 1*1000Mbps Uplink 1*1000Mbps SFP
PoE Standard	IEEE802.3 af / at
PoE Port	Port 1~4
Total Budget	65W MAX 72 W
PoE Pinout	1/2 V+ 3/6 V-

PoE port output	15.4 W MAX 30W
Type of forwarding	Storage forwarding
Bandwidth	10 G
MAC Address	2K, auto-learning & auto-aging
Standards	IEEE802.3,IEEE802.3u,IEEE802.3ab,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at
Transmission Distance	10BASE-T: Cat3/4/5 ≤250m 100BASE-TX: Cat5 ≤100m 1000BASE-T: Cat5e/Cat6 ≤100m SFP: MM 550m / SM 20~100km
Input voltage	AC 100-240V 50/60Hz
Operating Environment	Operating Temp: - 15℃~55℃; Storage Temp: -40℃~70℃ Operating Humidity: 10%~90% RH; Storage Humidity: 5%~90% RH, non-condensing
Size (L*W*H)	178*120*35 182*196*48mm
Weight	0.45/ 0.65Kg
Package specification	30SET W*D*H 415*580*275 21.5Kg
Installation Method	Desktop / Wall-mounted