RV-DP21HD

ACCESSORIES



Features
Compatible with all HD-CVI, HD-TVI, HD-AHD and Analog
Video and Power Solution;
Up to 250 meters for 3M/4M, 1080P AHD, 1080P HD-CVI and 1080P HD-TVI
Up to 430 meters for 720P CVI, 330 meters for 720P AHD and 250 meter for 720P TVI
Open on spot and easy adjustment
Convenient installation

Environment	Close-Circuit TV (HD CCTV) 1080P AHD/CVI/TVI and Analog
Normal Output Level	1Vp-p/ 75Ω
Bandwidth	Video: DC to 8 MHz.
Differential Gain	＜2%
Differential Phase	＜2 °
Weighted Signal-noise-ratio	60dB
Strong ability of anti-interference	surge protection: 6000V/1.2 μ S
Insertion Loss	Less than 0.5 dB per pair over the frequency range from DC to 6 MHz

Max. Distance 1080P, 3M/4M	250 meters for 1080P AHD/CVI/TVI
Max. Distance 720P	430 meters for 720P CVI, 330 meters for 720P AHD and 250 meter for 720P TVI
Connectors	RJ45 for video and 12VDC
BNC Connector	BNC male
Temperature	Operating: -10° to 70° C. Storage:-30° to 70° C. Humidity: up to 95%
Enclosure	ABS fire retardant plastic
Weight	40g (1.411oz)
Dimensions	Length 52 mm * Width 28mm * Height 21mm with 140mm cable