RV-DP22

ACCESSORIES



Features
PAL, NTSC, SECOM All-systems compatible;
Video-Audio/Data and Power Solution;
Up to 300 meters (1000 feet) via Category 5 unshielded twisted-pair cable
Open on spot and easy adjustment
Compact Size and Convenient installation

Environment	Close-Circuit TV (CCTV) equipment for security and surveillance.
Normal Output Level	1Vp-p/ 75Ω
Bandwidth	Video: DC to 8 MHz.
Differential Gain	＜ 2%
Differential Phase	＜ 2 °
Weighted Signal-noise-ratio	60dB
Strong ability of anti-interference	surge protection: 6000V/1.2 μ S
Insertion Loss	Less than 0.5 dB per pair over the frequency range from DC to 8 MHz
Max. Distance Color	Cat 3 –984 ft (300m); Cat 5 – 1,312 ft (400m)

Max. Distance Black & White	Cat 3 –1,640 ft(500m); Cat 5 – 2,296 ft (700m)
Connectors	RJ45 for Power-Video-Audio/Data
BNC Connector	BNC male
Temperature	Operating: -10° to 70° C. Storage:-30° to 70° C. Humidity: up to 95%
Enclosure	ABS fire retardant plastic
Weight	42g (1.48oz)
Dimensions	Length 52 mm * Width 28mm * Height 21mm with 140mm Cable